

General Air & Water

**EHA509**

Multipurpose - EPDM



**Application**

- For use with air, oil, hot or cold water and non-aggressive chemicals
- For dust control

**Markets**

- Construction
- Mining
- Rental industry
- Oil and gas exploration
- In-plant air service

**Construction**

- Tube** EPDM rubber
- Reinforcement** High-tensile synthetic textile
- Cover** EPDM rubber
- Color** Black

**Operating temperature**

-40°C to +120°C  
(-40°F to +248°F)

**Packaging**

300 ft  
Carton Box  
-10 Coil on Pallet

**Order Fulfillment**

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHA509-04	6.4	0.25	11	0.43	10.0	145	30	435	0.03	0.02	91.4	300
EHA509-05	7.9	0.31	14	0.55	10.0	145	30	435	0.05	0.03	91.4	300
EHA509-06	9.7	0.38	16	0.63	10.0	145	30	435	0.07	0.04	91.4	300
EHA509-08	12.7	0.50	20	0.79	10.0	145	30	435	0.08	0.05	91.4	300
EHA509-10	15.9	0.62	23	0.91	10.0	145	30	435	0.10	0.07	91.4	300
EHA509-12	19.0	0.75	27	1.06	10.0	145	30	435	0.12	0.08	91.4	300
EHA509-16	25.4	1.00	33	1.34	10.0	145	30	435	0.15	0.10	91.4	300

**Type of couplings**

- Hansen® Quick Connect
- Male barbed inserts

Contact coupling manufacturer for attachment procedure and other coupling recommendations