

Low Pressure

EHA504

Light Duty Air



Application

- Light duty air service
- Pneumatic tools

Markets

- Construction
- Mining
- Rental industry
- Oil and gas exploration
- In-plant air service

Construction

Tube Oil-mist resistant SBR rubber

Reinforcement

High-tensile synthetic textile

Cover Abrasion, ozone, and weather resistant SBR rubber blend

Colors Black (BK), Yellow (YW)

Operating temperature

-25°C to +70°C
(-13°F to +158°F)

Packaging

300 ft
Carton Box

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHA504-03BK	4.5	0.18	10.0	0.39	10.0	145	40.0	580	0.10	0.07	91.4	300
EHA504-04BK	6.0	0.25	11.0	0.43	10.0	145	40.0	580	0.11	0.07	91.4	300
EHA504-05BK	8.0	0.31	14.0	0.55	10.0	145	40.0	580	0.16	0.11	91.4	300
EHA504-06BK	10.0	0.39	16.0	0.63	10.0	145	40.0	580	0.19	0.13	91.4	300
EHA504-08BK	13.0	0.51	19.0	0.75	10.0	145	40.0	580	0.24	0.16	91.4	300
EHA504-10BK	16.0	0.63	23.0	0.91	10.0	145	40.0	580	0.34	0.23	91.4	300
EHA504-12BK	19.0	0.75	27.0	1.06	10.0	145	40.0	580	0.44	0.30	91.4	300
EHA504-16BK	25.0	1.00	34.0	1.34	10.0	145	40.0	580	0.64	0.43	91.4	300

Type of couplings

- Danfoss Quick Disconnect
- Male barbed inserts

Contact coupling manufacturer for attachment procedure and other coupling recommendations