

Low Pressure

H201
Easy Couple



Application

- Air and water transfer
- Pneumatic tools
- Air tools

Markets

- Oil and gas exploration
- Construction
- Mining
- Plastic molding

Construction

Tube Synthetic rubber (RMA Class A)

Reinforcement

1-braid fiber

Cover Synthetic rubber

Colors Black (BK), Blue (BU), Red (RD), Green (GR), Gray (GY) and Yellow (YW)

Certifications

RMA Class A tube
MSHA IC - 46/6 Black, MSHA IC - 84/62 Blue,
MSHA IC - 84/47 Red, MSHA IC - 84/48 Green,
MSHA IC - 84/64 Gray, MSHA IC - 84/63 Yellow

Operating temperature

Air and water

-40°C to +100°C (-40°F to +212°F)

Oil

-40°C to +127°C (-40°F to +260°F)

Packaging

50, 250, 500 ft

Order Fulfillment

Made to Stock

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
H20104BK-250R	6.4	0.25	12.7	0.50	20.7	300	83.0	1200	0.13	0.09	76.2	250
H20106BK-250R	9.5	0.38	17.0	0.67	20.7	300	83.0	1200	0.19	0.13	76.2	250
H20108BK-250R	12.7	0.50	19.6	0.77	20.7	300	83.0	1200	0.22	0.15	76.2	250
H20110BK-250R	15.9	0.62	23.6	0.93	20.7	300	83.0	1200	0.34	0.23	76.2	250
H20112BK-250R	19.0	0.75	26.3	1.04	20.7	300	83.0	1200	0.39	0.26	76.2	250
H20116BK-250R	25.4	1.00	35.0	1.38	13.8	200	55.0	800	0.57	0.38	76.2	250

Type of couplings

- Aeroquip® socketless
- Push-on couplings
- Danfoss B series
- Danfoss Quick disconnect

Contact coupling manufacturer for attachment procedure and other coupling recommendations