


Medium Pressure

EHA505

Medium Duty Air

**Application**

- Medium duty air service
- Pneumatic tools

Markets

- Construction
- Mining
- Rental industry
- Oil and gas exploration
- In-plant air service

Construction

Tube Oil-mist resistant SBR rubber

Reinforcement

High-tensile synthetic textile

Cover Abrasion, ozone, and weather resistant SBR rubber blend

Colors Black (BK), Yellow (YW)

Operating temperature

-25°C to +70°C
(-13°F to +158°F)

Packaging

300 ft
Carton Box
Product sold in bales with maximum three cut lengths in each bale

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHA505-04BK	6.0	0.25	13	0.51	20.0	290	64.0	928	0.16	0.11	91.4	300
EHA505-05BK	8.0	0.31	15	0.59	20.0	290	64.0	928	0.20	0.13	91.4	300
EHA505-06BK	10.0	0.39	18	0.71	20.0	290	64.0	928	0.27	0.18	91.4	300
EHA505-08BK	13.0	0.50	22	0.87	20.0	290	64.0	928	0.40	0.27	91.4	300
EHA505-10BK	16.0	0.63	25	0.98	20.0	290	64.0	928	0.45	0.30	91.4	300
EHA505-12BK	19.0	0.75	29	1.14	20.0	290	64.0	928	0.59	0.40	91.4	300
EHA505-16BK	25.0	1.00	37	1.46	20.0	290	64.0	928	1.89	1.27	91.4	300

Type of couplings

- Danfoss Quick Disconnect
- Male barbed inserts

Contact coupling manufacturer for attachment procedure and other coupling recommendations