

Welding

EHW500

Industrial Welding


Application

- For industrial welding with oxygen or acetylene

Markets

- In-plant service
- Welding

Construction

Tube SBR rubber blend

Reinforcement

High-tensile synthetic textile

Cover

Flame, abrasion, and weather resistant SBR rubber blend

Colors

Red (RD), Green (GN),
Blue (BU)

Certifications

ISO 3821

Operating temperature

-30°C to +80°C
(-22°F to +176°F)

Packaging

100 ft
Carton Box

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHW500-04RD	6.0	0.25	13.0	0.51	20.0	290	60.0	870	30	1.18	0.16	0.11	30.5	100
EHW500-04ARD	6.0	0.25	14.0	0.55	20.0	290	60.0	870	30	1.18	0.18	0.12	30.5	100
EHW500-05RD	8.0	0.31	15.0	0.59	20.0	290	60.0	870	40	1.57	0.19	0.13	30.5	100
EHW500-05ARD	8.0	0.31	16.0	0.63	20.0	290	60.0	870	40	1.57	0.22	0.15	30.5	100
EHW500M09RD	9.0	0.35	16.0	0.63	20.0	290	60.0	870	45	1.77	0.20	0.13	30.5	100
EHW500-06RD	10.0	0.38	17.0	0.67	20.0	290	60.0	870	50	1.97	0.22	0.15	30.5	100
EHW500-06ARD	10.0	0.38	18.0	0.71	20.0	290	60.0	870	50	1.97	0.26	0.17	30.5	100
EHW500-08RD	13.0	0.50	22.0	0.87	20.0	290	60.0	870	65	2.56	0.37	0.25	30.5	100

Type of couplings

Contact coupling manufacturer for attachment procedure and other coupling recommendations