

Specialty

**EHS540**

Sewer Jetting



**Application**

- For high pressure water cleaning and rinsing of sewage systems

**Markets**

- Waste management

**Construction**

**Tube** SBR rubber blend

**Reinforcement**

High-tensile synthetic textile

**Cover** SBR rubber blend

**Color** Black

**Operating temperature**

-40°C to +70°C

(-40°F to +158°F)

**Packaging**

500 ft

-08, -12 Carton Box

-16, -20 Coil on Pallet

**Order Fulfillment**

Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHS540-08	12.7	0.50	25.0	0.98	250	3625	625	9063	65	2.56	0.44	0.30	152.4	500
EHS540-12	19.0	0.75	31.6	1.24	250	3625	625	9063	90	3.54	0.56	0.38	152.4	500
EHS540-16	25.4	1.00	40.2	1.58	250	3625	625	9063	100	3.93	0.78	0.52	152.4	500
EHS540-20	32.0	1.25	48.0	1.89	250	3625	625	9063	130	5.12	1.06	0.71	152.4	500

**Type of couplings**

Contact coupling manufacturer for attachment procedure and other coupling recommendations