

Suction & Discharge



EHW150

Mink



Application

- Pumping, suction and discharge of water, mud and slurries
- Convey water in applications where oil resistance is needed on outer cover
- Transfer and haul salt water (brine)

Markets

- Construction
- Equipment rental
- Mining
- Ship building
- Oil and gas exploration
- Tank truck

Construction

Tube SBR rubber blend

Reinforcement

High tensile synthetic textile and steel helical wire

Cover Oil resistant NBR rubber blend

Color Black

Certifications

RMA Class B

Operating temperature

-25°C to +70°C
(-13°F to +158°F)

Packaging

100 ft

Order Fulfillment

Made to Stock
Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Vacuum		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kPa	in/Hg	kg/m	lbs/ft	mtr	ft
EHW150-20-100	31.8	1.25	42.0	1.65	10.5	150	31.5	450	125	4.92	94.8	28	0.85	0.57	30.5	100
EHW150-24-100	38.1	1.50	49.0	1.93	10.5	150	31.5	450	150	5.91	94.8	28	1.16	0.78	30.5	100
EHW150-32-100	50.8	2.00	63.0	2.48	10.5	150	31.5	450	215	8.46	94.8	28	1.71	1.15	30.5	100
EHW150-40-100	63.5	2.50	76.0	2.99	10.5	150	31.5	450	280	11.02	94.8	28	2.10	1.41	30.5	100
EHW150-48-100	76.2	3.00	89.0	3.50	10.5	150	31.5	450	350	13.78	94.8	28	2.64	1.77	30.5	100
EHW150-64-100	101.6	4.00	115.0	4.52	10.5	150	31.5	450	490	19.29	94.8	28	3.67	2.47	30.5	100
EHW150-96-100	152.4	6.00	168.0	6.61	10.5	150	31.5	450	760	29.92	94.8	28	7.09	4.76	30.5	100

Type of couplings

- Cam and groove
- Combination nipple

Contact coupling manufacturer for attachment procedure and other coupling recommendations